


## Transition joints between single **core cables**

Transition joints between **single core** paper insulated cable and extruded cable

respectively type (A)RG7H1R(X) and single pole cable made of paper impregnated with mixture type (A)RC1HLRX




Electrical performance:  
CEI 20-24 • CEI 20-62/2



Product	Voltage U <sub>max</sub> (kV)	Conductor cross section (mm <sup>2</sup> )		ENEL serial number
		paper cable	extruded cable	
GHVE 20/25-1-T	24		25	-
GHVE 20/240-1-T	24	50 - 240	35 - 185	271074
GHVE 20/400-1-T	24		240 - 400	-

Supplies do not include connectors which must be requested separately




Electrical performance:  
CEI 20-24 • CEI 20-62/2



Transition joints between **single core** paper insulated cable and extruded cable with aluminium sheet screen

type (A)RC1HLRX and type ARG7H5EXY

Product	Voltage U <sub>max</sub> (kV)	Conductor cross section (mm <sup>2</sup> )		ENEL serial number
		paper cable	extruded cable	
GHVE 20/240-1-TE	24	50 - 240	35 - 150	270118



Electrical performance:  
CEI 20-24 • HD 629-1



Transition joints between **single core** extruded cable with wire screen and extruded cable with aluminium foil screen

type (A)RG/H1R(X) or (A)RG7H1M1 and extruded single core cable type ARG7H5EXY

Product	Voltage U <sub>max</sub> (kV)	Conductor cross section		L max (mm)	D max (mm)
		from (mm <sup>2</sup> )	to (mm <sup>2</sup> )		
GHVE 20/240-1X-TE	24	25	240	1000	75