

Maxi Roll

Heat-shrink in maxi dispensers for industrial use.


Product	Colour	D (mm)	d (mm)	S (mm)	Lenght (m)
Maxi Roll 1,6	●	1,6	0,8	0,50	300
Maxi Roll 2,4	●	2,4	1,2	0,55	300
Maxi Roll 3,2	●	3,2	1,6	0,55	300
Maxi Roll 4,8	●	4,8	2,4	0,55	150
Maxi Roll 6,4	●	6,4	3,2	0,65	75
Maxi Roll 9,5	●	9,5	4,8	0,65	150
Maxi Roll 12,7	●	12,7	6,4	0,65	150
Maxi Roll 19,0	●	19,0	9,5	0,80	75
Maxi Roll 25,4	●	25,4	12,7	0,95	60



CGP-TEC

Sheath for commercial use.

Product	Colour	D (mm)	d (mm)	S (mm)	Spool (m)
CGP-TEC 1,2/0,6	●●●●○Ⓟ	1,2	0,6	0,45	600
CGP-TEC 1,6/0,8	●●●●○Ⓟ	1,6	0,8	0,45	300
CGP-TEC 2,4/1,2	●●●●○Ⓟ	2,4	1,2	0,50	300
CGP-TEC 3,2/1,6	●●●●○Ⓟ	3,2	1,6	0,50	300
CGP-TEC 4,8/2,4	●●●●○Ⓟ	4,8	2,4	0,50	150
CGP-TEC 6,4/3,2	●●●●○Ⓟ	6,4	3,2	0,65	75
CGP-TEC 9,5/4,8	●●●●○Ⓟ	9,5	4,8	0,65	150
CGP-TEC 12,7/6,4	●●●●○Ⓟ	12,7	6,4	0,65	150
CGP-TEC 19/9,5	●●●●○Ⓟ	19,0	9,5	0,75	75
CGP-TEC 25,4/12,7	●●●●○Ⓟ	25,4	12,7	0,90	60
CGP-TEC 38/19	●●●●○Ⓟ	38,0	19,0	1,00	60
CGP-TEC 51/26	●●●●○Ⓟ	51,0	26	1,15	30
CGP-TEC 76/38	●●●●○Ⓟ	76,0	38,0	1,27	15
CGP-TEC 102/51	●●●●○Ⓟ	102,0	51,0	1,40	15



DCP-TEC

Sheath suitable for coating grounding cables.

Product	Colour	D (mm)	d (mm)	S (mm)	Spool (m)
DCP-TEC 3/1,5	●●	3,0	1,5	0,51	300
DCP-TEC 6/3	●●	6,0	3,0	0,58	75
DCP-TEC 10/5	●●	10,0	5,0	0,64	75
DCP-TEC 12/6	●●	12,0	6,0	0,64	75
DCP-TEC 19/9	●●	19,0	9,0	0,74	75
DCP-TEC 26/13	●●	26,0	13,0	0,89	30
DCP-TEC 38/19	●●	38,0	19,0	1,00	30

