



Operating temperature **90°**

Installation temperature: **-40°C / +50°C**

## Rapid Joint IP68 System Fast RP

Straight joint pre-filled with gel.

Product	Formation n°	Configuration IP68			Configuration IPX8		
		Section mm <sup>2</sup>	Ø cable mm	A x B (mm)	Section mm <sup>2</sup>	Ø cable mm	A x B (mm)
Rapid Joint L6-RIP68/1	o	25 - 50	12 - 18	245 x 60	<del>25 - 50</del>	24	180 x 60
Rapid Joint L6-RIP68/2	oo	1,5 - 10	12 - 18		<del>1,5 - 10</del>	24	
Rapid Joint L6-RIP68/3	oo	1,5 - 6	12 - 18		<del>1,5 - 10</del>	24	
Rapid Joint L6-RIP68/4	oo	1,5 - 6	12 - 18		<del>1,5 - 10</del>	24	
Rapid Joint L10-RIP68/1	o	70 - 95	16 - 20	275 x 65	35 - 150	31	210 x 65
Rapid Joint L10-RIP68/2	oo	10 - 16	16 - 20		10 - 25	31	
Rapid Joint L10-RIP68/3	oo	10	16 - 20		10 - 25	31	
Rapid Joint L10-RIP68/4	oo	10	16 - 20		10 - 25	31	



Installation temperature: **-40°C / +50°C**

Operating temperature **90°**

## Rapid Joint System Fast RP

Straight joint pre-filled with gel.

Product	Cable formation from 2x a 4x (n° x mm <sup>2</sup> )	Dimensions A x B (mm)
Rapid Joint L 10 RP	1,5 - 10	180 x 60
Rapid Joint L 25 RP	10 - 25	210 x 65
Rapid Joint L 95 RP	35 - 95	320 x 100



Operating temperature **90°**

Installation temperature: **-40°C / +50°C**

## Magic Power Joint System Fast RP

Straight joint with Magic Power Gel.

Product	Cable formation from 2x a 4x (n° x mm <sup>2</sup> )	Dimensions A x B (mm)
Magic P Joint L 35- RP/16	1,5 - 16	232 x 70
Magic P Joint L 35- RP/35	10 - 35	232 x 70
Magic P Joint L 50- RP/50	25 - 50	266 x 72
Magic P Joint L 120- RP/120	35 - 120	365 x 95
Magic P Joint L 240- RP/150	35 - 150	510 x 120